



Installer Kit System - Packing List

Revised 03-08-16

S/N: _____ INV: _____ DATE: _____

REPAIRING (Pipe I.D.): (Ft/mm) 1.5/38, 2.0/50, 3.0/75, 4.0/102, 5.0/127, 6.0/152 or Other: _____

REPAIRING (Pipe material/type): Rigid/Flex PVC, HDPE, Metal or Other: _____

USING Liner Lengths: Standard (Ft/mtr) 10/3, 15/4.6, 25/7.6, 35/10.7, 40/12.2, 50/15 or Other: _____

USING Liner I.D.: (In/mm) 1.0/25, 1.125/30, 1.5/38, 2.0/50, 3.0/75, 4.0/102, 5.0/127 or Other: _____

Hardware Contents:

(2) Retainer sleeves

OR

(2) Encasement sleeves

(1) Liquid soap Lubricant (amber) for liner head section & wax lube (yellow) for tag line length

(1) Warning label -"DO NOT CUT or Heat"

(1) Reference Sheets: Step x Step Checklist, Liquid Soap/Wax Lubricant if needed

(1) 1.5' x 3' poly plastic mat

(1) 1.5" or 2.0" MPT x soc (436-015/020) and (1) FPT x Socket (435-015/020)

OR

(1) For HDPE pipe (equipment side) repair MPT x Insert (1436-015/020) and

(1) FPT x Socket (435-015/020) and

(1) S/S screw clamp for HDPE (Black Poly) Fitting

Epoxy Contents:

(4) Latex gloves

(1 or 2) 2-part (1:1) waterproof syringe epoxy for underwater or dry applications

(1 or 2) 2-part (1:1) Gray and white epoxy for non-sag damp or dry applications (Cures underwater)

(2) Epoxy stirring sticks

(1) Sanding cloth

(2) Alcohol packets

Liner Contents (If Applicable): ISO 9001rated

(1) 1.0", 1.125" or 1.5" or other: _____ I.D. Liner made of EPDM_vulcanizate, Santoprene NSF61 Rated

(1) Type 1 Solid PVC liner head section sealed to tag line (Installed onto liner)

(1) Type 1 Solid PVC liner tail section with 1/4" NPT male nipple (installed onto liner)

(1) 1/2" width x 10,15, 25, 35, 50 ft. length or other: _____ flat nylon tag line sealed to liner head section